

LED Motion Sensor Tube Lights Clear - 1.2m 18W

Introduction: Geric Holdings Led lighting

When human motion is detected, the Motion sensor turns the Tube Light on. When the person(s) leaves the Tube Light proximity, the light is automatically switched off. Great for additional electricity savings.



Application:

Widely used in hotels, conference rooms, offices, residential and institutional buildings, schools, universities, hospitals.

Features:

- ♣ Complete electricity isolation design, safety proven.
- Input AC to DC constant current diver. There is no need for outer ballast, more safety.
- Comply with ROHS, no mercury or any other harmful substance.

Specifications:

| Model No. | 18-TL-WH-C-5042-M (Cool White) | 18-TL-WW-C-120-MS-5417 (Warm White) | 18-TL-NW-C-120-MS-5026 (Nature White) |
|--------------------------------|-----------------------------------|--|--|
| Color temperature | 6000±500K | 3000±200K | 4000±250K |
| Luminous Flux | 2376LM | 1926LM | 2136LM |
| Input voltage | AC85 - 277V | | |
| Power Factor (PF) | >0.95 | | |
| Total power | 18W | | |
| CRI (Color Rendering Index) | >80 | >80 | >80 |
| Size | 120cm (4 feet) | | |
| Lifespan | 50,000 hours | | |
| Warranty | 3years | | |





LED Motion Sensor Tube Lights Frosted - 1.5m 20W

Introduction: Geric Holdings Led lighting

When human motion is detected, the Motion sensor turns the Tube Light on. When the person(s) leaves the Tube Light proximity, the light is automatically switched off. Great for additional electricity savings.



Application:

Widely used in hotels, conference rooms, offices, residential and institutional buildings, schools, universities, hospitals.

Features:

- ♣ Complete electricity isolation design, safety proven.
- Input AC to DC constant current diver. There is no need for outer ballast, more safety.
- ♣ Comply with ROHS, no mercury or any other harmful substance.

Specifications:

| Model No. | 27-TL-WH-F-5051-M (Cool White) | 27-TL-WW-F-150-MS-5444 (Warm White) | 27-TL-NW-F-150-MS-5441 (Natural White) |
|--------------------------------|-----------------------------------|--|---|
| Color temperature | 6000±500K | 3000±200K | 4000±250K |
| Luminous Flux | 2790LM | 2248LM | 2524LM |
| Input voltage | AC85-277V | | |
| Power Factor (PF) | >0.95 | | |
| Total power | 20W | | |
| CRI (Color Rendering Index) | >80 | | |
| Size | 150cm (5 feet) | | |
| Lifespan | 50,000 hours | | |
| Warranty | 3 years | | |

