



40W Standalone LED Street Light with Integrated Solar Panel and Aluminium body

Standalone easy to maintain LED Street Light requiring no remote telemetry or an individual remote control since it will be always on automatic operation at FULL power from dusk to dawn. A true install it and forget about it energy saving solution ideal for remote areas. Although always at full power when on, this light will be fully functional for a minimum of 2 days even if rainy weather persists resulting in no charging of its highly efficient lithium iron phosphate battery during this time period.









Geric Holdings Led lighting

Specifications

Lighting power: 40W LED Lumens output: 4400lm

Operating Brightness level: Always at Full Brightness

LED Efficiency: 150 lm/W **LED Color temperature (CCT):** 6000 K

LED Light distribution: Asymmetric Batwing

Product weight: 10.36 kg

 Product size:
 89 cm x 40 cm x 11 cm

 Packing size:
 103.5 cm x 45 cm x 11.5 cm

Solar panels: 6V80W monocrystalline silicon panels
Battery type: Sanyuan Lithium Ion electric vehicle battery

Battery capacity: 54.5Ah @ 13.2V

Operating range: -35° to 60° ; Wind speeds up to 120 km/h; RH up to 95%

Mounting Method: Variable angle clamp onto pole. Pole not included.

Mounting height: 5-7 m

Light Supply circuit:Constant Current controlledRainy days:2-3 days autonomy at full power

Minimum Solar Insolation: 3.5 kWh/m²

Light body material: die-cast aluminium

Enclosure structure: Integrated Solar panels and passively cooled battery.

Waterproof grade: IP65


LED life-time: 50,000 hours

Warranty: 2 and 3 year options available











ISOCANDELA DIAGRAM showing Asymmetric Batwing light distribution

