

## LED Tube Lights - 60cm (2 feet) 10W

### Introduction: Geric Holdings Led lighting

LOCAL ASSEMBLY! OWN Patented 1.2mm wall aluminium tube with ADVANCED Heat Dissipation. LED tube lights are solid state, high shock/vibration resistant lights. A high-performance constant driver makes them highly efficient. Its installation is safe and convenient. They offer a 70%-80% cost saving over fluorescent tube lights over a period of time. We offer a full range of sizes to replace 60cm, 90cm, 120cm and 150cm traditional lamps. Our tube lights are SABS tested!



Clear



Frosted

### Application:

- Widely used in hotels, conference rooms, offices, residential and institutional buildings, schools, universities, hospitals.

### Features:

- Complete electricity isolation design, safety proven.
- Input AC to DC constant current diver. There is no need for outer ballast, more safe.
- Comply with ROHS, no mercury or any other harmful substance.

### Parameters :

Model No. (Clear Cover)	10-TL-WH-C-5036	10-TL-WW-C-5037	10-TL-NW-C-5038
Model No. (Frosted Cover)	10-TL-WH-F-5039	10-TL-WW-F-5040	10-TL-NW-F-5041
Color temperature	6000±500K (Cool White)	3000±200K (Warm White)	4000±250K (Natural White)
Luminous Flux Clear	1300LM	1169LM	1234LM
Luminous Flux Frosted	1267LM	1139LM	1203LM
Input voltage	85 - 277V		
Power Factor (PF)	>0.97		
Total power	10W		
CRI (Color Rendering Index)	>80		
Size	60cm (2 feet)		
Lifespan	50,000 hours		
Warranty	3 years		

## LED Tube Lights - 120cm (4 feet) 18W

### Introduction: Geric Holdings Led lighting

LOCAL ASSEMBLY! OWN Patented 1.2mm wall aluminium tube with ADVANCED Heat Dissipation. LED tube lights are solid state, high shock/vibration resistant lights. A high-performance constant driver makes them highly efficient. Its installation is safe and convenient. They offer a 70%-80% cost saving over fluorescent tube lights over a period of time. We offer a full range of sizes to replace 60cm, 90cm, 120cm and 150cm traditional lamps. Our tube lights are SABS tested!



Clear



Frosted

### Application:

- Widely used in hotels, conference rooms, offices, residential and institutional buildings, schools, universities, hospitals.

### Features:

- Complete electricity isolation design, safety proven.
- Input AC to DC constant current diver. There is no need for outer ballast, more safe.
- Comply with ROHS, no mercury or any other harmful substance.

### Parameters :

Model No. (Clear Cover)	18-TL-WH-C-5042	18-TL-WW-C-5043	18-TL-NW-C-5044
Model No. (Frosted Cover)	18-TL-WH-F-5045	18-TL-WW-F-5046	18-TL-NW-F-5047
Color temperature	6000±500K (Cool White)	3000±200K (Warm White)	4000±250K (Natural White)
Luminous Flux Clear	2340LM	2104LM	2222LM
Luminous Flux Frosted	2281LM	2050LM	2166LM
Input voltage	85 - 277V		
Power Factor (PF)	>0.97		
Total power	18W		
CRI (Color Rendering Index)	>80		
Size	120cm (4 feet)		
Lifespan	50,000 hours		
Warranty	3 years		

## LED Tube Lights - 150cm (5 feet) 27W

### Introduction: Geric Holdings Led lighting

LOCAL ASSEMBLY! OWN Patented 1.2mm wall aluminium tube with ADVANCED Heat Dissipation. LED tube lights are solid state, high shock/vibration resistant lights. A high-performance constant driver makes them highly efficient. Its installation is safe and convenient. They offer a 70%-80% cost saving over fluorescent tube lights over a period of time. We offer a full range of sizes to replace 60cm, 90cm, 120cm and 150cm traditional lamps. Our tube lights are SABS tested!



Clear



Frosted

### Application:

- Widely used in hotels, conference rooms, offices, residential and institutional buildings, schools, universities, hospitals.

### Features:

- Complete electricity isolation design, safety proven.
- Input AC to DC constant current driver. There is no need for outer ballast, more safe.
- Comply with ROHS, no mercury or any other harmful substance.

### Parameters :

Model No. (Clear Cover)	27-TL-WH-C-5048	27-TL-WW-C-5049	27-TL-NW-C-5050
Model No. (Frosted Cover)	27-TL-WH-F-5051	27-TL-WW-F-5052	27-TL-NW-F-5053
Color temperature	6000±500K (Cool White)	3000±200K (Warm White)	4000±250K (Natural White)
Luminous Flux Clear	3510LM	3155LM	3333LM
Luminous Flux Frosted	3421LM	3076LM	3248LM
Input voltage	85 - 277V		
Power Factor (PF)	>0.97		
Total power	27W		
CRI (Color Rendering Index)	>80		
Size	150cm (5 feet)		
Lifespan	50,000 hours		
Warranty	3 years		

## LED Tube Lights - 150cm (5 feet) 15W

### Introduction: Geric Holdings Led lighting

LOCAL ASSEMBLY! OWN Patented 1.2mm wall aluminium tube with ADVANCED Heat Dissipation. LED tube lights are solid state, high shock/vibration resistant lights. A high-performance constant driver makes them highly efficient. Its installation is safe and convenient. They offer a 70%-80% cost saving over fluorescent tube lights over a period of time. We offer a full range of sizes to replace 60cm, 90cm, 120cm and 150cm traditional lamps. Our tube lights are SABS tested!



Frosted

### Application:

- Widely used in hotels, conference rooms, offices, residential and institutional buildings, schools, universities, hospitals.

### Features:

- Complete electricity isolation design, safety proven.
- Input AC to DC constant current driver. There is no need for outer ballast, more safe.
- Comply with ROHS, no mercury or any other harmful substance.

### Parameters :

Model No.	15-TL-WH-F-5146
Cover	Frosted
Color temperature	6000±500K (Cool White)
Luminous Flux Frosted	1900LM
Input voltage	85-277V
Power Factor (PF)	>0.94
Total power	15W
CRI (Color Rendering Index)	>80
Size	150cm (5 feet)
Lifespan	50,000 hours
Warranty	3 years

## LED Tube Lights - 150cm (5 feet) 18W

### Introduction: Geric Holdings Led lighting

LOCAL ASSEMBLY! OWN Patented 1.2mm wall aluminium tube with ADVANCED Heat Dissipation. LED tube lights are solid state, high shock/vibration resistant lights. A high-performance constant driver makes them highly efficient. Its installation is safe and convenient. They offer a 70%-80% cost saving over fluorescent tube lights over a period of time. We offer a full range of sizes to replace 60cm, 90cm, 120cm and 150cm traditional lamps. Our tube lights are SABS tested!



Frosted

### Application:

- Widely used in hotels, conference rooms, offices, residential and institutional buildings, schools, universities, hospitals.

### Features:

- Complete electricity isolation design, safety proven.
- Input AC to DC constant current driver. There is no need for outer ballast, more safe.
- Comply with ROHS, no mercury or any other harmful substance.

### Parameters :

Model No.	18-TL-WH-F-5024
Cover	Frosted
Color temperature	6000±500K (Cool White)
Luminous Flux Frosted	2280LM
Input voltage	85-277V
Power Factor (PF)	>0.94
Total power	18W
CRI (Color Rendering Index)	>80
Size	150cm (5 feet)
Lifespan	50,000 hours
Warranty	3 years

Last Updated: 2017-07-18

